

Keypad Door Control Station

Cat. 6406

DESCRIPTION

The Jeron Keypad Door Control Station is used with the Jeron Pro-Alert™ 640 System to arm and disarm door switch zones to permit authorized staff entry and exit.

FEATURES

- Two Color Status LED Indicator
- Two Access Codes: Timed and Alternate Action
- Remote Timer Bypass
- Provision for External Dome Light
- Microprocessor Controlled

OPERATION

When the Door Control Station is armed, the Status LED color is steady red. When a connected door switch zone is activated, the Status LED flashes red and an urgent level call is placed on the system activating all associated visual and audible indicators. The unit has two modes of arming: Timed and Alternate Action.

Timed Mode

If the preprogrammed Timed Mode access code is entered on the keypad, the zone will disarm for the preprogrammed time interval and the Status LED color will change to green. While disarmed, the door switch zone may change state without causing an alarm condition. When the time interval has elapsed, the zone will automatically rearm and the Status LED color will change to steady red.



In the Timed Mode, a momentary switch connected to the Remote Access Switch input may be used to disarm the zone for the pre-programmed interval from a location accessible only to staff.

Alternate Action Mode

If the preprogrammed Alternate Action Mode access code is entered on the keypad, the zone will disarm and remain in that state until rearmed by entering either the Timed or Alternate Action preprogrammed access codes. Rearming with the Alternate Action code causes the zone to arm immediately. The Timed code will rearm the zone after the preprogrammed time interval elapses to allow staff to exit.

EQUIPMENT

The Keypad Door Control Station is furnished on a two-gang white trimplate equipped with a twelve button keypad and bi-color LED indicator. The unit may be mounted on a one or two-gang back-box.

TECHNICAL DATA

Dimensions (H x W x D):

- 4.5 x 4.5 x 2.5 in.
(11.3 x 11.3 x 6.4 cm)

Back-box Required:

- Raco 670RAC 1-gang or 232 with 2-gang ring

Controls/Indicators:

- 12 Keys: 0-9, #, *
- Bi-color LED: red, green

Operating Voltage:

- 28 VDC @ 10 mA

Termination:

- Plug-in IDC

Arm/Disarm Code:

- Four digits, 0000 to 9999;
10,000 codes for each mode

Time Range Interval:

- 99 seconds

PRODUCT SUBJECT TO CHANGE WITHOUT NOTIFICATION.